

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
6 May 2005 (06.05.2005)

PCT

(10) International Publication Number  
**WO 2005/039745 A1**

(51) International Patent Classification<sup>7</sup>: **B01F 3/08**, 5/16,  
7/00, 13/10, B01J 27/138, 37/00, F04D 1/06

(74) Agent: **SACCO, Marco**; Basell Poliolefine Italia S.p.A.,  
Intellectual Property, P.le G.Donegani 12, I-44100 Ferrara  
(IT).

(21) International Application Number:  
PCT/EP2004/010943

(22) International Filing Date:  
30 September 2004 (30.09.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
03103838.3 16 October 2003 (16.10.2003) EP  
60/512,640 20 October 2003 (20.10.2003) US

(71) Applicant (for all designated States except US): **BASELL  
POLIOLEFINE ITALIA S.p.A.** [IT/IT]; Via Pergolesi  
25, I-20124 Milano (IT).

(72) Inventors; and


(75) Inventors/Applicants (for US only): **ARLETTI, Arrigo**  
[IT/IT]; Via Mazzini, 8, I-41034 Finale Emilia - Modena  
(IT). **VINCENZI, Paolo** [IT/IT]; Via A. Gramsci, 284/A,  
I-45036 Ficarolo - Rovigo (IT).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,  
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: PROCESS FOR THE CONTINUOUS PRODUCTION OF EMULSIONS



(57) Abstract: A multistage process for the continuous production of an emulsion comprising subjecting at least two immiscible liquids to a sequence of at least two mixing stages carried out in at least two successive stator-rotor devices (4), wherein a peripheral outlet from a first stator-rotor device (8, 12) is connected to an axial inlet (9, 13) in the successive stator-rotor device by means of a duct in which the Reynold number  $Re_T$  inside said duct is higher than 5000, and the peripheral velocity of each rotor of said stator-rotor devices ranges from 5 to 60 m/s.



**Declaration under Rule 4.17:**

— *of inventorship (Rule 4.17(iv)) for US only*

**Published:**

— *with international search report*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*